

# QUICKSTART® INJECT + FRAC VALVE

## Innovation revealed

The QuickStart® Inject + Frac Valve provides the operator with an initial point to break down the formation and established a pump-in port for use in long horizontal completions. The device is comprised of an opening piston that is controlled by a special rupture disc.

The QuickStart Frac Valve(s) are run as an integral part of the casing string and may be utilized in both cemented and un-cemented well bores.

## Features

- One piece mandrel design providing a very robust tool. Burst pressure rating up to 20,000 psi
- Port Jetting™ Technology improves injectivity to formation
- Opening sequence is controlled by a fit for purpose rupture disc that is designed to resist the plugging or bridging at the membrane
- Mandrel design with TORQ Thru Technology maintains casing string integrity and yield torque ratings. The tool can be “through torqued” onto the casing string for ease of make up
- High torque casing connections for ease in matching any number of today’s requirements
- Exceeds all safety and environmental standards



The device is comprised of an opening piston that is controlled by a special rupture disc.

## QUICKSTART® INJECT + FRAC VALVE SPECS

Part Number	Connection Size	Max O.D.	Min I.D.	Make Up Length (ft)	Temp Rating °F	Flow Area	Torque Rating ft/lbs	Working Pressure
TC-QS-450-0000	4.5"	5.65"	3.34"	4	325°	6.8	15,000	19,000
TC-QS-450-0000-SE	4.5"	5.65"	3.34"	4	375°	6.8	15,000	19,000
TC-QS-455-0000	5"	5.65"	3.34"	4	325°	6.8	15,000	19,000
TC-QS-455-0000-SE	5"	5.65"	3.34"	4	375°	6.8	15,000	19,000
TC-QS-551-0000	5.5."	6.5"	3.75"	5.25	325°	7.5	20,000	20,000
TC-QS-551-0000-SE	5.5."	6.5"	3.75"	5.25	375°	7.5	20,000	20,000
TC-QS-580-0000	5.5."	7.38"	4.6"	4	325°	7.5	20,000	20,000
TC-QS-587-0000	5.5."	7.38"	4.67"	4	325°	7.5	20,000	20,000

\*375°F seals available upon request.

For more information, and to find a representative near you, [visit nineenergyservice.com](https://www.nineenergyservice.com)